




Tubes COOL-FIT 2.0

Exécution:

- PE100 SDR11 pré isolé, métrique
- Isolation en mousse GF HE
- Résistant aux impacts Couleur: noir
- Avec bouts lisses pour l'électrosoudage

Remarque:

Plus grandes dimensions disponibles dans la gamme de produits COOL-FIT 4.0



d/D (mm)	DN (mm)	PN (bar)	Code	Poids (kg/m)	di (mm)	L (mm)	L1 (mm)	Pouce (inch)
32/75	25	16	738 174 108	1.140	26.2	5000	36	1
40/90	32	16	738 174 109	1.534	32.6	5000	40	1 ½
50/90	40	16	738 174 110	1.722	40.8	5000	44	1 ½
63/110	50	16	738 174 111	2.711	51.4	5000	48	2
75/125	65	16	738 174 112	3.405	61.4	5000	55	2 ½
90/140	80	16	738 174 113	4.320	73.5	5000	62	3
110/160	100	16	738 174 114	5.692	90.0	5000	72	4
140/200	125	16	738 174 116	9.021	114.6	5000	84	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>