



Manchon COOL-FIT 2.0

Exécution:

- PE100 SDR11 pré isolé, métrique
- Isolation en mousse GF HE
- Résistant aux impacts Couleur : noir
- Lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur

Remarque:

Plus grandes dimensions disponibles dans la gamme de produits COOL-FIT 4.0

d/D (mm)	PN (bar)	Code	Poids (kg)	L (mm)	L1 (mm)	z (mm)	Pouce (inch)
32/75	16	738 914 108	0.092	113	36	5	1
40/90	16	738 914 109	0.126	121	40	3	1 ¼
50/90	16	738 914 110	0.160	129	44	3	1 ½
63/110	16	738 914 111	0.237	137	48	3	2
75/125	16	738 914 112	0.339	152	55	3	2 ½
90/140	16	738 914 113	0.476	166	62	4	3
110/160	16	738 914 114	0.778	188	72	4	4
140/200	16	738 914 116	1.097	210	84	3	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>