





A



B



A



B

## Coude à 90° COOL-FIT 2.0

### Exécution:

- PE100 SDR11 pré isolé, métrique
- Isolation en mousse GF HE
- Résistant aux impacts Couleur : noir
- A: Raccord électrosoudable avec lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur
- B: Raccord à bout lisse

d/D (mm)	PN (bar)	Code	Poids (kg)	L (mm)	L1 (mm)	z (mm)	Pouce (inch)	Type
32/75	16	<b>738 104 108</b>	0.127	75	36	20	1	A
40/90	16	<b>738 104 109</b>	0.185	82	40	23	1 ¼	A
50/90	16	<b>738 104 110</b>	0.242	93	44	30	1 ½	A
63/110	16	<b>738 104 111</b>	0.384	101	48	34	2	A
75/125	16	<b>738 104 112</b>	0.510	114	55	40	2 ½	A
90/140	16	<b>738 104 113</b>	0.960	144	62	63	3	A
110/160	16	<b>738 104 114</b>	1.406	168	72	77	4	A
140/200	16	<b>738 104 116</b>	2.690		84	221	5	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>