

Coudes à 45° COOL-FIT 2.0

Exécution:

- PE100 SDR11 pré isolé, métrique
- Isolation en mousse GF HE
- Résistant aux impacts Couleur : noir
- A: Raccord électrosoudable avec lèvres d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur
- B: Raccord à bout lisse




A




B

d/D (mm)	PN (bar)	Code	Poids (kg)	L (mm)	L1 (mm)	z (mm)	Pouce (inch)	Type
32/75	16	738 154 108	0.101	66	36	11	1	A
40/90	16	738 154 109	0.143	70	40	11	1 ¼	A
50/90	16	738 154 110	0.206	76	44	13	1 ½	A
63/110	16	738 154 111	0.307	83	48	16	2	A
75/125	16	738 154 112	0.407	92	55	18	2 ½	A
90/140	16	738 154 113	0.686	111	62	30	3	A
110/160	16	738 154 114	1.123	132	72	41	4	A
140/200	16	738 154 116	1.967		84	164	5	B



A



B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>