





A



B



A



B

Té réduit à 90° COOL-FIT 2.0

Exécution:

- PE100 SDR11 pré isolé, métrique
- Isolation en mousse GF HE
- Résistant aux impacts Couleur: noir
- A: Raccord électrosoudable avec lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur à bout lisse.
- B: Raccord à bout lisse

| d/D (mm) | d1/D1 (mm) | PN (bar) | Code | Poids (kg) | L (mm) | L1 (mm) | L2 (mm) | z (mm) | z1 (mm) | Closest inch (inch) | Type |
|-------------|---------------|-------------|--------------------|---------------|-----------|------------|------------|-----------|------------|------------------------|------|
| 75/125 | 63/110 | 16 | 738 204 218 | 0.746 | 110 | 55 | 48 | 36 | 200 | 2 ½ - 2 | A |
| 90/140 | 63/110 | 16 | 738 204 222 | 1.096 | 124 | 62 | 48 | 42 | 227 | 3 - 2 | A |
| 90/140 | 75/125 | 16 | 738 204 223 | 1.133 | 124 | 62 | 55 | 42 | 227 | 3 - 2 ½ | A |
| 110/160 | 63/110 | 16 | 738 204 227 | 1.746 | 148 | 72 | 48 | 57 | 245 | 4 - 2 | A |
| 110/160 | 75/125 | 16 | 738 204 228 | 1.782 | 148 | 72 | 55 | 57 | 245 | 4 - 2 ½ | A |
| 110/160 | 90/140 | 16 | 738 204 229 | 1.848 | 148 | 72 | 62 | 57 | 245 | 4 - 3 | A |
| 140/200 | 63/110 | 16 | 738 204 340 | 3.441 | | 84 | 48 | 198 | 250 | 5 - 2 | B |
| 140/200 | 75/125 | 16 | 738 204 341 | 3.504 | | 84 | 55 | 198 | 262 | 5 - 2 ½ | B |
| 140/200 | 90/140 | 16 | 738 204 342 | 3.569 | | 84 | 62 | 198 | 263 | 5 - 3 | B |
| 140/200 | 110/160 | 16 | 738 204 343 | 3.620 | | 84 | 72 | 198 | 258 | 5 - 4 | B |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>