



Tubes DEKADUR-Vent PVC-U

Exécution:

- Matériel: PVC-U
- Dimension: Selon DIN 8062
- Couleur: Gris foncé RAL 7011
- Longueur de tube: 5m, à bouts lisses
- Prévention incendie: Ignifuge selon DIN 4102 B1 jusqu'à une épaisseur de paroi de 3,2 mm
- **Note 1:** Variations de dimensions de l'épaisseur de paroi non conforme à DIN 8062
- **Note 2:** Egalement disponible en longueurs de 5900mm
- **Note 3:** Disponible seulement en barres de 5900mm
- Attention: Sur demande tubes de ventilation avec charge extérieure (dépression).

Note	d (mm)	Code	Poids (kg)	e (mm)
2	110	324 110 000	0.964	1.8
	125	324 125 000	1.100	1.8
	140	324 140 000	1.230	1.8
	160	324 160 000	1.410	1.8
	180	324 180 000	1.590	1.8
	200	324 200 000	1.770	1.8
	225	324 225 000	1.990	1.8
	250	324 250 000	2.430	2.0
	280	324 280 000	3.030	2.2
2	315	324 315 000	3.830	2.5
2	355	324 355 000	4.790	2.8
2	400	324 400 000	6.190	3.2
	450	324 450 000	7.760	3.6
	500	324 500 000	9.510	4.0
1,2	160	324 160 001	1.929	2.5
1	180	324 180 001	2.174	2.5
1,2	200	324 200 001	2.420	2.5
1,2	225	324 225 001	3.020	2.8
1	250	324 250 002	3.469	2.9
1,3	250	324 250 003	3.033	2.5
1	280	324 280 001	3.890	2.9
1	315	324 315 001	4.328	2.9
1	355	324 355 001	7.442	4.4
1	400	324 400 001	9.419	5.0
1	450	324 450 001	11.884	5.6
1	500	324 500 001	13.223	5.6
1	600	324 600 000	14.192	5.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>