



Tubes PVC-U, gris Série S 4, SDR 9, pression nominale PN 25

Exécution:

- SDR 9 / High Performance
- Matériel: PVC-U
- Dimension: acc. to DIN 8061/62
- Colour: darkgrey RAL 7011
- Pipe length: 5000mm, with plain ends
- **Note 1:** DIBT Z-40.23-1 approval
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

Note	d (mm)	PN (bar)	Code	poids (kg/m)	e (mm)
1	6	16	161 017 126	0,025	1,0
1	8	16	161 017 127	0,035	1,0
1	10	16	161 017 128	0,054	1,2
1	12	16	161 017 129	0,074	1,4
1	16	16	161 017 130	0,125	1,8
1	20	16	161 017 131	0,199	2,3
1	25	16	161 017 132	0,299	2,8
1	32	16	161 017 133	0,489	3,6
1	40	16	161 017 134	0,761	4,5
1	50	16	161 017 135	1,180	5,6
1	63	16	161 017 136	1,880	7,1
1	75	16	161 017 137	2,640	8,4
1	90	16	161 017 138	3,800	10,1
1	110	16	161 017 139	5,560	12,3

Les données techniques ne sont pas des "contraintes techniques". Elles ne représentent aucune caractéristiques garanties ni ne garantissent aucune propriétés d'une durabilité garantie. Elles sont soumises à des modifications. Nos conditions générales de vente sont applicables.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>