



Tubes PVC-U, gris SDR 34.3, pression nominale PN 6

Exécution:

- SDR 34,4 / PN 6 / S 16,7
- Matériel: PVC-U
- Dimension: acc. to DIN 8061/62
- Colour: darkgrey RAL 7011
- Pipe length: 5000mm, with plain ends
- **Note 1:** DIBT Z-40.23-1 approval
- **Note 2:** according to DIN 8062
- **Note 3:** DVGW approval + DIN plus
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentaion). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

Note	d (mm)	PN (bar)	Code	poids (kg/m)	e (mm)
2	50	6	161 017 060	0,366	1,5
2	63	6	161 017 061	0,571	1,9
2	75	6	161 017 062	0,793	2,2
2	90	6	161 017 063	1,150	2,7
2	110	6	161 017 064	1,660	3,2
2	125	6	161 017 065	2,160	3,7
2	140	6	161 017 066	2,690	4,1
2	160	6	161 017 067	3,490	4,7
2	180	6	161 017 068	4,430	5,3
2	200	6	161 017 069	5,440	5,9
2	225	6	161 017 070	6,850	6,6
2	250	6	161 017 071	8,430	7,3
2	315	6	161 017 072	13,300	9,2
2	355	6	161 017 073	17,000	10,4
2	400	6	161 017 074	21,400	11,7

Les données techniques ne sont pas des "contraintes techniques". Elles ne représentent aucune caractéristiques garanties ni ne garantissent aucune propriétés d'une durabilité garantie . Elles sont soumises à des modifications . Nos conditions générales de vente sont applicables.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>