





The system

PROGEF – more than a system

The outstanding material for any challenge in industrial applications

We are dedicated to designing, manufacturing and marketing piping systems for the safe and secure treatment or conveyance of water, liquids, chemicals and gases. As a leading piping systems provider with global presence, we offer our customers not only reliable and innovative products of highest quality, but we supply also tailor-made solutions from one source. In close coordination with end-customers and based on their needs, GF Piping Systems introduced the PROGEF family, a specified polypropylene system based on certified raw material, serving a wide variety of industrial applications. Thanks to its beneficial mechanical properties, chemical resistance, outstanding weldability and especially its high resistance to thermal distortion, the PROGEF systems guarantee a maximum of safety, reliability and performance.



Individuality – from the planning stage to installation

PROGEF Welded Systems are ideally adapted to customer needs

Whether installed above or below ground, our system meets any demanding requirement, in every phase of the project, worldwide. Therefore, the variety of our product portfolio is as diverse as our customers and their individual challenges. Together with high level services such as technical support, low- or single-item customizing production and training courses, our specific system range generates exceptional added value for our customers.

With a comprehensive piping system solution, comprised of pipes, fittings, valves, related jointing as well as automation technologies in high quality thermoplastics, GF Piping Systems provides the right fit and quality for many industrial media conveyance systems and for many industrial applications.

Customizing

The focus of our worldwide located customizing teams is manufacturing custom parts for special systems. Standardized processes guarantee the highest level of quality.

Technical support

Technical support such as material selection is a key factor for a successful installation. A team of experts is available for individual support all around the world.







Pipes

Fittings

Manual valves

PROGEF Standard – for a wide range of industrial applications

The highly resistant system offers numerous fields of application in industries. High stress fracture, pressure, abrasion, corrosion and temperature resistance are only some of the advantageous characteristic properties for the durable polypropylene system. Its fine, homogeneous material structure furthermore offers outstanding weldability and low heat distortion.



PROGEF Plus – for defined water qualities and clean applications

Cleaned and packed in specified processes, the silicone-free or oil-free PROGEF Plus system has a high pureness factor. The system is widely used in demanding applications in microelectronics or coating and surface treatment, where features such as an outstanding surface finish and excellent leach-out characteristics offer additional benefit. The components are double-bagged to ensure cleanliness and prevent contamination before installation.



PROGEF Natural – for laboratories and pharmaceutical applications

Wherever pure solutions are needed, especially for applications in chemical or life science industries, PROGEF Natural is predestined. Beneficial properties of the transparent, pigment-free polypropylene such as excellent clean, smooth surface, high chemical and temperature resistance, and additionally the bead and crevice free jointing technologies, ensure highest system quality.



Technical documentation

Our extensive know-how of more than 50 years is fully documented in detail in our technical manuals, planning fundamentals and application guides.

Chemical resistance

In the area of chemical resistance our specialist teams offer individual support and advice in selecting the right material for the corresponding requirements.



+GF+





Customizing and training

Online and mobile calculation tools

Our numerous online and mobile calculation tools, available in many different languages, support our customers in configuring and commissioning automation products.

CAD library

The extensive CAD library is the most frequently used planning tool. The freely available database comprises over 30 000 drawings as well as technical data for our customers. Many formats are available.

Training courses and on-site training

Offering a wide range of training courses we provide participants an excellent opportunity to gain confidence in working with our products and proven jointing technologies.

System lifetime warranty *

Confirming confidence in the premium quality of our Polypropylene product and system range, we grant a limited system lifetime warranty.

* Detailed information regarding the warranty can be found under: www.gfps.com - Planning fundamentals



Automation

System range

Everything from one source

With a constant focus on maximum reliability and safety the PROGEF systems assure a sustained high level of product quality and outstanding performance standards in all applications. The clearly defined development and manufacturing processes of our worldwide specified systems are carried out on the basis of all relevant standards and specifications and are regularly audited and evaluated to achieve continuous improvement. Certified processes as well as product approvals are part of the active and sustainable quality management system of GF Piping Systems and makes us a reliable partner. Therefore, with our PROGEF welded system range, our customers can be assured that their needs are covered and comply with necessary standards.

PROGEF Standard & PROGEF Plus

Products		d	16	20	25	32	40	20	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	450	200	260	630
	SDR	DN PN	10	15	20	25	32	40	20	92	80	100	100	125	150	150	200	200	250	250	300	350	400	450	200	200	500	400 430
	7.4	16						-	_		_	_														-		
Pipes	11	10																										
	17.6	6																								200		
Socket fusion fittings	11	10												-														
Butt fusion fittings,	11	10							10																			
Infrared (IR) compatible	17.6	6																										
	11	10																										
Ball valves	17.6	6												-			-											_
	11	10																									\exists	
Diaphragm valves	17.6	6																										
Butterfly valves		10																										
Check vales	11/17.6	10																										
Check vales	11	10																								-		
Pressure regulating valves	11	10																										
Ventilating and bleed valve		10																					-		-		-	
Automation							\	/arie	s be	twee	en pr	oduc	cts															
Flanges PP-V / PP-steel																	-											
Flange seals EPDM / FKM																												
Pipe clips PP / PE																								-		-	_	
PROGEF Standard PROGEF F	Plus															·								,	·			
Welding machines		d	16	20	25	32	40	20	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	450	200	260	430
Socket fusion machines																												
Butt fusion machines																												
Infrared (IR) fusion machines																												

4



* Standards:







PROGEF Standard & PROGEF Plus

Systems	PROGEF Standard	PROGEF Plus
Material	- d16–d315 ß PP-H 100 (ß Polypropylene Homopolymer) - d355–d500 state-of-the-art PP	- d20-d315 ß PP-H 100 (ß Polypropylene Homopolymer)
Colour	RAL 7032	RAL 7032
Density	~ 0.90 g / cm³ (ISO 1183 / ASTM D 792)	~0.90 g / cm ³ (ISO 1183/ASTM D 792)
Thermal expansion coefficient	0.16mm / mK (DIN 53752)	0.16mm / mK (DIN 53752)
Thermal conductivity	0.23W / mK (EN 12664)	0.23W / mK (EN 12664)
Surface resistivity	> 1016 Ω (IEC 60093)	> 1016 Ω (IEC 60093)
Dimensions	d16-d500 in accordance to EN ISO 15494	d20-d315 in accordance to EN ISO 15494
Surface condition	accordance to EN ISO 15494	- Inner surface Ra < 1.0 μm (39μin) for components d20–d110 - Inner surface Ra < 1.5 μm (59μin) for components d125–d315
Material- and product-approvals	FDA CFR 21 177.1520 USP 25 class VI (physiological non-toxic) DIBt (Z-40.23-4, Z-40.34-264, Z - 40.23-265) DNV (K-2630, K - 2636) Loyd's Register (01/20030(E1)) UL94HB (horizontal burning)	FDA CFR 21 177.1520 USP 25 class VI (physiological non-toxic) UL94HB (horizontal burning)
Packaging	pipes, fittings and valves bulk bagged	pipes, fittings and valves, each component double bagged
Marking	 brand name product description article number material dimensions standards and approvals 	 brand name product description article number material dimensions standards and approvals

* Approvals / Acceptance:











^{*} The most significant standards and approvals are shown above. An overview of all approvals online: www.gfps.com

System range & system specification



* Standards:







PROGEF Natural

										_					
Products		d	20		32			63		90	_				
	SDR	PN DN	15	20	25	32	40	50	65	80	100				
Pipes	11	10										System	PROGEF Natural		
	17.6	6										Material	d20-d110 PP-R (Polypropy-		
Butt fusion fittings, Infrared (IR) compatible	11	10											lene Random Copolymer)		
	17.6	6										Colour	pigment-free, transparent		
Sanitary adapter	11	10										Density	~ 0.90g / cm³ (ISO 1183/ ASTM D 792)		
Ball valves PP-H body/PP-R	11	10										Thermal expansion			
Ball valves PP-H Flange connections		10										coefficient	0.16mm / mK (DIN 53752)		
Diaphragm valves PP-R	11	10										Thermal conductivity	0.23W / mK (EN 12664)		
Diaphragm valves PP-H Flange connections		10										Surface resistivity	> 1016 Ω (IEC 60093)		
Butterfly valves PP-H		10										Dimensions	d20-d110 according to EN ISO 15494		
Cone check vales PP-H body/PP-R	11	10										Surface condition	Inner surface: Ra < 1.0 μm (39μin)		
Cone check vales PP-H Flange connections		10											FDA CFR 21 177.1520		
Automation										ipor que		Material- and product approvals	USP 25 class VI (physiologica		
Flanges PP-V / PP-steel										440			non-toxic) Food conformity (D		
Flange seals EPDM / FKM													pipes, fittings and valves,		
Pipe clips PP / PE												Packaging	each component single bagged		
Welding machines		d	20	25	32	70	20	63	75	06	110		- brand name - product description - article number		
Butt fusion machines												Marking	- material		
Infrared (IR) fusion machines													dimensionsstandards and approvals		
BCF fusion machine															

* Approvals / Acceptance:





* Sanitary adaptor Standards: ISO, DIN, ASME BPE, 3A, JIS An overview of all approvals online: www.gfps.com

^{*} The most significant standards and approvals are shown.

Jointing methods

Proven technologies for your installation

A large diversity of innovative and intelligent welding solutions enriched with global training and service offerings

As a pioneer in the field, GF Piping Systems has always been placing a high priority on developing innovative jointing techniques to fulfill specific requirements and materials in use. Simplicity in application, chemical resistance, thermal stability and long-term weld strength are the key drivers in our jointing technologies. With a global jointing training program, international machine rental and a world-wide network of service centres, our customers benefit from expert know-how and practical experience.

Welding technology

Socket fusion – the strong connection

The fast and reliable solution to produce heavy-duty connections, in the workshop or the field.

Butt fusion – the economical connection

Economical and flexible fusion especially for larger diameters. From manual machines to full CNC control with traceability.

IR- (Infrared) fusion – the fast, clean connection

Fast, repeatable and clean welds via non-contact heating. Full traceability of the welding process, with user quidance.

BCF-Plus fusion – the smooth connection

Bead and Crevice Free jointing with the highest weld factor, lowest stress and completely smooth fusion zone without any intrusions.

Welding machine









Joint cross-section











Macro-image









For more information about training courses from GF Piping Systems please contact our local sales companies.

Specifications

Exceeding quality standards

Technical specifications with focus on pressure-/temperature attributes

PROGEF Systems*

Standard - Plus - Natural


PROGEF Systems out of polypropylene show excellent physical properties and mechanical characteristics, indicating its status as a highly versatile and universal solution. Having a high operational temperature range and ensuring outstanding chemical resistance, high abrasion resistance and high impact strength values, the material meets all requirements of demanding industrial conditions or environments.

Furthermore, properties such as low weight, low density, minimum internal stresses and an excellent smooth internal surface with high finish quality, make PROGEF systems a high-grade piping material.


According to the 10°C line in the hydrostatic strength curve for PP, a permissible pressure of 12.0 bar/7.4 bar in the temperature range of 0°C to 10°C for the SDR11/PN10 and SDR17.6/PN6 system can be applied.

- P Permissible pressure in bar, psi
- T Temperature in °C (Celsius), °F (Fahrenheit)

PROGEF Standard (PP) and PROGEF Plus (PP)



PROGEF Natural (PP-R)



The pressure-/temperature curve based on medium water, operating temperature of 20 °C, valid life time of 25 years and the design factor C = 2.

Pressure-Temperature Diagram

Pressure-Temperature Diagram

^{*} More information regarding technical specifications can be found online in our planning fundamentals: www.gfps.com

Chemical resistance

For your operational safety

Polypropylene (PP) - a high quality material with outstanding characteristics for a safe and efficient operation



Professional material technology

Chemical resistance at 20 (Applications can be very d	°C ependent on the concentration)		illy crys rmopla:			phous plastics	Stainle	ss Steel
Media	Chemicals	PP	PE	PVDF	PVC-U	PVC-C	1.4401 316	1.4301 304
	HNO ₃ ≤ 25 %	0	0	+	+	+	0	0
Oxidizing Acids	25 % ≤ HNO ₃ ≤ 65 %	-	0	+	0	+	0	0
(HNO ₃ , H ₂ CrO ₄ ,	H ₂ CrO ₄ aqueous solution	0	0	+	0	0	0	0
H ₂ SO ₄ , etc.)	H ₂ SO ₄ ≤ 70%	+	+	+	+	+	-	-
	70 % ≤ H ₂ SO ₄ ≤ 96 %	-	-	+	+	+	-	_
Non Oxidizing Acids (HCl, HF, etc.)	HCl ≤ 30 %	+	+	+	+	+	0	_
	HF ≤ 40 %	+	+	+	+	-	0	-
(Hot, Hi , etc.)	40 % ≤ HF ≤ 75 %	+	+	+	_	-	0 0 0 0 -	-
	HCOOH ≤ 25 %	+	+	+	+	+	0	_
Organic	25 % ≤ HCOOH ≤ tech. pure	+	+	+	+	-	0	-
(formic acid, acetic acid, citric acid, etc.)	CH ₃ COOH <u><</u> 50 %	+	+	+	+	+	0	-
	$50\% \leq CH_3COOH \leq tech. pure$	+	+	+	0	-	0	-
	C ₃ H ₄ OH (COOH) ₃	+	+	+	+	+	0	-
Bases	Inorganic (NaOH, KOH, etc.)	+	+	-	+	0	+	+
Bases	Organic (amine, imidazole, etc.)	+	+	-	0	-	0	0
Salts	NaCl, FeCl ₂ , FeCl ₃ , CaCl ₂ , etc.	+	+	+	+	+	0	0
Halogens	Chlorine, bromine, iodine, (no fluorine)	-	-	0	0	0	0	-
E 1 /0"	Aliphatic hydrocarbons	0	0	+	+	0	+	+
Fuels / Oils	Aromatic hydrocarbons	-	-	+	_	-	+	+
	Chlorinated hydrocarbons	_	-	0	-	-	0	0
	Ketones	+	+	0	-	-	+	+
Solvents	Alcohols	+	+	+	0	-	+	+
	Esters	0	0	0	-	-	+	+
	Aldehydes	+	+	-	-	-	+	+
Phenols	Phenol, Cresol, etc.	+	+	+	_	-	+	

+ resistant 0 conditionally resistant, please consult us - not resistant


Please note: The above list is only intended as a guideline and does not replace an indepth review of material suitability for the particular application. The information is based on our experience and is state of the art. These data are general indicators only. In practice, however, other factors such as concentration, pressure and jointing technology must also be taken into consideration. The technical data are not binding and are not expressly warranted characteristics of the goods.

The smarter way of automation

Automation made easy

A unique system-based approach that bundles and integrates competencies, knowledge, best-in-class resources and technologies

With an innovative product portfolio in the field of measurement, control and actuation devices, GF Piping Systems consistently follows its system approach. The complete solution combines measurement, control and actuation technology together with high quality piping systems and represents a unique form of product and competence bundling. The system-integrated devices that measure values such as temperature, pressure and flow delivering accuracy, productivity, reliability and safety to customers in a wide range of industries. Providing the entire range of automation technology from simple instrument panels to complex measurement installations, GF Piping Systems has not only the product resources and the technical expertise, but also the global service and support infrastructure needed to meet the high customer requirements.



As versatile as your applications

Leading applications enabled by safe and reliable systems adapted to fit the needs of demanding industries

GF Piping Systems develops customized best-in-class solutions, aligned to the specific requirements of our customers in various sectors of industry, enabling profitable operation. Most notably our systems are ideally suited for the water treatment, pharmaceutical and chemical process industry, in fields of microelectronics and energy as well as in food & beverage production. With our system knowledge and product expertise, we support our customers during the planning process, the sustainable realization of the projects and provide valuable added services. Expertise in developing and producing piping systems, combined with profound industry and market knowledge, based on longstanding experience, makes GF Piping Systems a qualified and professional partner for our customers.

Applications of Highest Security in Chemical Industry

The usage of PROGEF Standard systems in chemical processes strengthens the industries approach of manufacturing and conveying chemical media in the safest and at the same time most economical way.



in Microelectronics

Wherever defined water qualities and controlled processes are required PROGEF Plus offers reliable and economical system solutions. With PROGEF Plus high purity water specifications and quality standards are dependably met.

Clean Water Applications



Demanding Applications in Water Treatment

With PROGEF system, application processes in water treatment can be designed reliable and of highest efficiency. Thereby, challenges such as guaranteeing high water quality and assuring stringent regulations can be faced.





Highly Specialised Applications in Energy Production

For secure processing in water chemical applications PROGEF Standard system combines high performance utilization with outstanding material properties. This leads to a beneficial gain in conditions of safety and health.

11 +GF+

Worldwide at home

Our sales companies and representatives ensure local customer support in more than 100 countries.

www.gfps.com

Argentina / Southern South America Georg Fischer Central Plastics Sudamérica S.R.L. Buenos Aires, Argentina Phone +54 11 4512 02 90 gfcentral.ps.ar@georgfischer.com www.gfps.com/ar

George Fischer Pty Ltd Riverwood NSW 2210 Australia Phone +61 (0) 2 9502 8000 australia.ps@georgfischer.com www.gfps.com/au

Austria

Georg Fischer Rohrleitungssysteme GmbH 3130 Herzogenburg Phone +43 (0) 2782 856 43-0 austria.ps@georgfischer.com www.gfps.com/at

Belgium / Luxembourg

Belgium/Luxembourg Georg Fischer NV/SA 1600 Sint-Pieters-Leeuw/Belgium Phone +32 (0) 2 556 40 20 Fax +32 (0) 2 524 34 26 be.ps@georgfischer.com www.gfps.com/be

Georg Fischer Sist. de Tub. Ltda. 04571-020 São Paulo/SP Phone +55 (0) 11 5525 1311 br.ps@georafischer.com www.gfps.com/br

Canada

Georg Fischer Piping Systems Ltd Mississauga, ON L5T 2B2 Phone +1 (905) 670 8005 Fax +1 (905) 670 8513 ca.ps@georgfischer.com www.gfps.com/ca

Georg Fischer Piping Systems Ltd Shanghai 201319 Phone +86 21 3899 3899 china.ps@georgfischer.com www.gfps.com/cn

Denmark / Iceland

Georg Fischer A/S 2630 Taastrup Phone +45 (0) 70 22 19 75 info.dk.ps@georgfischer.com www.gfps.com/dk

Finland

Finland Georg Fischer AB 01510 VANTAA Phone +358 (0) 9 586 58 25 Fax +358 (0) 9 586 58 29 info.fi.ps@georgfischer.com www.gfps.com/fi

Georg Fischer SAS 95932 Roissy Charles de Gaulle Cedex Phone +33 (0) 1 41 84 68 84 fr.ps@georgfischer.com www.gfps.com/fr

Germany Georg Fischer GmbH 73095 Albershausen Phone +49 (0) 7161 302 0 info.de.ps@georafischer.com www.gfps.com/de

India

Georg Fischer Piping Systems Pvt. Ltd 400 083 Mumbai Phone +91 22 4007 2000 Fax +91 22 4007 2020 branchoffice@georgfischer.com www.gfps.com/in

Indonesia PT Georg Fischer Indonesia Karawang 41371, Jawa Barat Phone +62 267 432 044 Fax +62 267 431 857 indonesia.ps@georgfischer.com www.gfps.com/id

Georg Fischer S.p.A. 20063 Cernusco S/N (MI) Phone +39 02 921 861 it.ps@georgfischer.com www.gfps.com/it

Georg Fischer Ltd 530-0003 Osaka Phone +81 (0) 6 6341 2451 jp.ps@georgfischer.com www.gfps.com/jp

Georg Fischer Korea Co. Ltd Unit 2501, U-Tower 120 HeungdeokJungang-ro (Yeongdeok-dong) Giheung-gu, Yongin-si, Gyeonggi-do Phone +82 31 8017 1450 Fax +82 31 217 1454 kor.ps@georgfischer.com www.gfps.com/kr

Malaysia George Fischer (M) Sdn. Bhd. 40460 Shah Alam, Selangor Darul Ehsan Phone +60 (0) 3 5122 5585 Fax +60 (0) 3 5122 5575 my.ps@georgfischer.com www.qfps.com/my

Mexico / Northern Latin America

Georg Fischer S.A. de C.V. Apodaca, Nuevo Leon CP66636 Mexico Phone +52 (81) 1340 8586 Fax +52 (81) 1522 8906 mx.ps@georgfischer.com www.gfps.com/mx

Middle East Georg Fischer Piping Systems (Switzerland) Ltd Dubai, United Arab Emirates Phone +971 4 289 49 60 gcc.ps@georgfischer.com www.afps.com/int

Netherlands Georg Fischer N.V. 8161 PA Epe Phone +31 (0) 578 678 222 nl.ps@georgfischer.com www.gfps.com/nl

Norway Georg Fischer AS 1351 Rud Phone +47 67 18 29 00 no.ps@georgfischer.com www.gfps.com/no

Philippines

George Fischer Pte Ltd Representative Office Phone +632 571 2365 Fax +632 571 2368 sgp.ps@georgfischer.com www.gfps.com/sg

Poland Georg Fischer Sp. z o.o. 05-090 Sekocin Nowy Phone +48 (0) 22 31 31 0 50 poland.ps@georgfischer.com www.gfps.com/pl

Romania

Georg Fischer Piping Systems (Switzerland) Ltd 020257 Bucharest - Sector 2 Phone +40 (0) 21 230 53 80 ro.ps@georgfischer.com www.gfps.com/int

Georg Fischer Piping Systems (Switzerland) Ltd Moscow 125040 Phone +7 495 748 11 44 ru.ps@georgfischer.com www.gfps.com/ru

Singapore George Fischer Pte Ltd 11 Tampines Street 92, #04-01/07 528 872 Singapore Phone +65 6747 0611 Fax +65 6747 0577 sgp.ps@georgfischer.com www.gfps.com/sg

Spain / Portugal Georg Fischer S.A. 28046 Madrid Phone +34 (0) 91 781 98 90 es.ps@georgfischer.com www.afps.com/es

Sweden Georg Fischer AB 117 43 Stockholm Phone +46 (0) 8 506 775 00 info.se.ps@georgfischer.com www.gfps.com/se

Switzerland

Georg Fischer Rohrleitungssysteme (Schweiz) AG 8201 Schaffhausen Phone +41 (0) 52 631 3026 ch.ps@georgfischer.com www.gfps.com/ch

Taiwan

Taiwan
Georg Fischer Co. Ltd
San Chung Dist., New Taipei City
Phone +886 2 8512 2822
Fax +886 2 8512 2823 www.gfps.com/tw

United Kingdom / Ireland George Fischer Sales Limited Coventry, CV2 2ST Phone +44 (0) 2476 535 535 uk.ps@georgfischer.com www.gfps.com/uk

USA / Caribbean

Georg Fischer LLC 9271 Jeronimo Road 92618 Irvine, CA Phone +1 714 731 8800 Fax +1 714 731 6201 us.ps@georgfischer.com www.gfps.com/us

International
Georg Fischer Piping Systems (Switzerland) Ltd
8201 Schaffhausen/Switzerland
Phone +41 (0) 52 631 3003
Fax +41 (0) 52 631 2893 info.export@georgfischer.com www.gfps.com/int

The information and technical data (altogether "Data") herein are not binding, unless explicitly confirmed in writing.

The Data neither constitutes any expressed, implied or warranted characteristics, nor guaranteed properties or a guaranteed durability. All Data is subject to modification. The General Terms and Conditions of Sale of Georg Fischer Piping Systems apply.

